

**Name:** 12s-8-13  
**Type:** Butterfly control valves  
**Subtype:** Medium parameters valves  
**Operating medium:** air-gas  
**Body material:** 20



#### DESCRIPTION:

Butterfly control valves have shutoff and control disk shaped device turning about an axis at a required angle to the direction of controlled fluid flow. Also these valves can be called as paddle valve , butterfly gate, hermetic valve, hermetically sealed valve, sealed valve. Butterfly control valves are widely used as isolation valves with respect to big diameter pipelines, low pressure and nonstrict requirements for operating device leaktightness.

#### TECHNICAL DATA:

Diameter, DN: 1200 mm  
Pressure, PN: 0.1 MPa  
Temperature: 400 СЉ  
Maximum pressure differential: 0.1 MPa  
Discharge rate (Kv100): 10000 m<sup>3</sup>/h  
Rotational moment on the shaft: 1600 Ngm  
Operating stroke: 0.25 mm

#### DIMENSIONS:

D1: 1210 mm  
D2: - mm  
D3: - mm  
L: 260 mm  
H: 1483 mm  
Weight: 269 кг

#### ACTUATOR:

Control type: P  
Actuator model: МЭО-4000/63-0,25У-97К У2  
Actuator power: 0.32 kW  
Full stroke time: 41 s

DIMENSIONAL DRAWING:

