


Name: DRF-7-40-8-E5-22

Russian name: ВЦП 7-40 №8 Исп.5, 22 кВт

Type: Dust-exhaust fans

Notes: It is recommended to use vibration isolators of CVI-43 type in quantity of 5 pcs.



DESCRIPTION:

Dust-exhaust fans of DRF-7-40 type are widely used in general purpose air ventilation systems, in dust-trapping units, in granular material pneumatic conveying systems, in grain processing lines, in dust-loaded air bleed systems within cement and reinforced concrete structure production. Also these fans are used for wood chips and saw-dust removal, for metal dust suction, for slag and dust removal in welding industry and for other industrial and sanitary-engineering purposes. These medium pressure fans are manufactured in right-hand and left-hand rotations with radial blades. In accordance with the field of application these fans can be produced in the following modifications:

 - general purpose industrial modification (carbon steel)

 - corrosion-resistant modification (stainless steel)

 - corrosion-resistant modification (titanium alloys)

AERODYNAMIC PERFORMANCE:

Capacity: 16.5 ths. m³

Total pressure: 2430 Pa

Temperature: 80 C

Efficiency: 50-58 %

Dustiness: 600.0 g/m³

DIMENSIONS:

Length: 2200 mm

Width: 985 mm

Height: 1312 mm

Weight: 700 kg

ELECTRIC MOTOR:

Power: 22 kW

Rate speed: 1430 rpm

Moment of inertia: n/a kg*m²

AUXILIARIES:

Actuator: n/a Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

