


Name: FDFB-10-1000**Russian name:** БДН-10-1000**Type:** Single inlet centrifugal FD fans of FDFB type**Notes:** Backward curved blades. Running wheel on the electric motor shaft.**DESCRIPTION:**

Single inlet centrifugal FD Fans are used for air delivery into combustion chambers of boilers with the capacity of 2.5- 950 t/h operating with balanced draft (secondary blast). It is allowed to use these fans in processing systems to handle air with the temperature not more than 70 °C. Single inlet centrifugal FD Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The blades of impeller are backward curved.

AERODYNAMIC PERFORMANCE:Capacity: 13.6 ths. m³

Total pressure: 1550 Pa

Temperature: 30 C

Efficiency: 83 %

Dustiness: 0.1 g/m³**DIMENSIONS:**

Length: 1288 mm

Width: 1825 mm

Height: 1485 mm

Weight: 625 kg

ELECTRIC MOTOR:

Power: 11 kW

Rate speed: 1000 rpm

Moment of inertia: 13,62 kg*m²**AUXILIARIES:**

Actuator: 100 Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

