

Name: FDFB-36x2-EM

Russian name: ВДН-36x2-Э

Type: Double inlet centrifugal FD fans of FDFB type

Notes: Backward curved blades



DESCRIPTION:

Double inlet centrifugal FD Fans are designed for air delivery into combustion chambers of pressure-fired boilers with the capacity of up to 2500 t/h. High-pressure FD Fans overcome full resistance of air-gas flow path. Double inlet centrifugal FD Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The blades of impeller are backward curved.

AERODYNAMIC PERFORMANCE:

Capacity: 1330.0 ths. m³

Total pressure: 8820 Pa

Temperature: 100 C

Efficiency: 88 %

Dustiness: 0.1 g/m³

DIMENSIONS:

Length: 6916 mm

Width: 4450 mm

Height: 5235 mm

Weight: 65 000 kg

ELECTRIC MOTOR:

Power: 4000 kW

Rate speed: 750 rpm

Moment of inertia: 12750 kg*m²

AUXILIARIES:

Actuator: 4000 Hm

DELIVERY OPTIONS:

Railway: Flatcar: 4 | Open wagon: 1 | Schnabel car: 1

DIMENSIONAL DRAWING:

