

**Name:** HPRF-240-26-4-E1-11

**Russian name:** BP 12-26 №4 ИСП.1, 11 кВт

**Type:** High pressure radial fans

**Notes:** It is recommended to use vibration isolators of CVI-39 type in quantity of 5 pcs.



## DESCRIPTION:

High pressure radial fans of HPRF-240-26 type are widely used in air ventilation, air-heating and air conditioning systems of industrial and civil buildings, in processing lines and for other industrial and sanitary-engineering purposes. These high pressure fans are manufactured in right-hand and left-hand rotations with backward curved blades. In accordance with the field of application these fans can be produced in the following modifications:

- <br> - general purpose industrial modification (carbon steel)
- <br> - corrosion-resistant modification (stainless steel)
- <br> - explosion-proof modification (dissimilar metals)
- <br> - explosion-proof and corrosion-resistant modification (dissimilar metals)
- <br> - corrosion-resistant modification (titanium alloys)

## AERODYNAMIC PERFORMANCE:

Capacity: 4.5 ths. m<sup>3</sup>  
Total pressure: 4800 Pa  
Temperature: 80 C  
Efficiency: 56-63 %  
Dustiness: 0.1 g/m<sup>3</sup>

## DIMENSIONS:

Length: 663 mm  
Width: 618 mm  
Height: 645 mm  
Weight: 105 kg

## ELECTRIC MOTOR:

Power: 11 kW  
Rate speed: 3000 rpm  
Moment of inertia: n/a kg\*m<sup>2</sup>

**AUXILIARIES:**

Actuator: n/a Hm

**DELIVERY OPTIONS:**

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

**DIMENSIONAL DRAWING:**

