


Name: IDF-H-20

Russian name: ГД-20

Type: Single inlet centrifugal hot-blast ID fans

Notes: Forward curved blades



DESCRIPTION:

Single inlet centrifugal hot-blast ID Fans are designed for flue gases recirculation in solid fuel or gas-and-oil-fired boilers. It is allowed to use such hot-blast fans for removal hot and dust-loaded gases from furnaces in pelletized ore production, ferrous metallurgy and sintering plants. In view of operation under high temperature these fans are made of heat-resistant steel. Single inlet centrifugal hot-blast ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The main units of these Fans are: running wheel, running gear, scroll casing, inlet bell and axial guide vanes.

AERODYNAMIC PERFORMANCE:

Capacity: 200.0 ths. m³

Total pressure: 5250 Pa

Temperature: 400 C

Efficiency: 72 %

Dustiness: 1.0 g/m³

DIMENSIONS:

Length: 3230 mm

Width: 3430 mm

Height: 3050 mm

Weight: 5320 kg

ELECTRIC MOTOR:

Power: 500 kW

Rate speed: 1000 rpm

Moment of inertia: 670 kg*m²

AUXILIARIES:

Actuator: 630 Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

