

Name: IDF-H-25-M

Russian name: ГД-25М

Type: Single inlet centrifugal hot-blast ID fans

Notes: Backward curved blades



DESCRIPTION:

Single inlet centrifugal hot-blast ID Fans are designed for flue gases recirculation in solid fuel or gas-and-oil-fired boilers. It is allowed to use such hot-blast fans for removal hot and dust-loaded gases from furnaces in pelletized ore production, ferrous metallurgy and sintering plants. In view of operation under high temperature these fans are made of heat-resistant steel. Single inlet centrifugal hot-blast ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The main units of these Fans are: running wheel, running gear, scroll casing, inlet bell and axial guide vanes.

AERODYNAMIC PERFORMANCE:

Capacity: 298.0 ths. m³

Total pressure: 5639 Pa

Temperature: 400 C

Efficiency: 81 %

Dustiness: 0.5 g/m³

DIMENSIONS:

Length: 3225 mm

Width: 5357 mm

Height: 4255 mm

Weight: 6 200 kg

ELECTRIC MOTOR:

Power: 630 kW

Rate speed: 1000 rpm

Moment of inertia: 920 kg*m²

AUXILIARIES:

Actuator: 630 Hm

DELIVERY OPTIONS:

Railway: Flatcar: 2 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

