


Name: IDFB-11.2-1500
Russian name: ДН-11,2-1500
Type: Single inlet centrifugal ID fans of IDFB type
Notes: Backward curved blades



DESCRIPTION:

Single inlet centrifugal ID Fans are intended to be used for flue gas removal from combustion chambers of solid fuel or gas-and-oil-fired boilers equipped with dry ash catchers. It is allowed to install such ID Fans in processing systems for handling compatible gases (The dustiness should be not more than 2 g/m³, abrasion and sticking tendency should be similar to ashed flue gases). Such ID Fans can be applied for single or serial-parallel operation. Double inlet centrifugal ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The main units of Single inlet centrifugal ID Fan are: running wheel, running gear, scroll casing, inlet bell and axial guide vanes. The blades of impeller are backward curved.

AERODYNAMIC PERFORMANCE:

Capacity: 28.7 ths. m³
Total pressure: 281 Pa
Temperature: 200 C
Efficiency: 83 %
Dustiness: 2.0 g/m³

DIMENSIONS:

Length: 1477 mm
Width: 2038 mm
Height: 1685 mm
Weight: 765 kg

ELECTRIC MOTOR:

Power: 45 kW
Rate speed: 1500 rpm
Moment of inertia: 32 kg*m²

AUXILIARIES:
Actuator: 250 Hm

DELIVERY OPTIONS:
Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

