

Name: IDFB-22-F-C-OG

Russian name: ДН-22ФКГМ

Type: Single inlet centrifugal high pressure ID fans

Notes: Backward curved blades



DESCRIPTION:

Single inlet high-pressure ID Fans are designed for flue gas removal from combustion chambers of steam boilers with the capacity of up to 480 t/h with increased resistance of flue gas path. It is also allowed to install such ID Fans in processing systems for handling compatible gases (The dustiness should be not more than 2 g/m³, abrasion and sticking tendency should be similar to ashed flue gases). Also these fans are recommended to handle gases containing trace elements with sticking tendency. The blades of impeller are backward curved.

AERODYNAMIC PERFORMANCE:

Capacity: 121.0 ths. m³

Total pressure: 4840 Pa

Temperature: 250 C

Efficiency: 78 %

Dustiness: 2.0 g/m³

DIMENSIONS:

Length: 3390 mm

Width: 4360 mm

Height: 3430 mm

Weight: 6350 kg

ELECTRIC MOTOR:

Power: 250 kW

Rate speed: 750 rpm

Moment of inertia: 750 kg*m²

AUXILIARIES:

Actuator: 630 Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

