


Name: IDFB-22x2-0.62-OG

Russian name: ДН-22x2-0,62ГМ

Type: Double inlet centrifugal ID fans of IDFB type

Notes: Backward curved blades



DESCRIPTION:

Double inlet centrifugal ID Fans are intended to be used for flue gas removal from combustion chambers of solid fuel or gas-and-oil-fired boilers with the capacity of up to 480 t/h equipped with dry ash catchers. It is allowed to install such ID Fans in processing systems for handling compatible gases (The dustiness should be not more than 2 g/m³, abrasion and sticking tendency should be similar to ashed flue gases). Such ID Fans can be applied for single or serial-parallel operation. Double inlet centrifugal ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The main units of Double inlet centrifugal ID Fan are: running wheel, running gear, scroll casing, two inlet boxes and two guide vanes. The blades of impeller are backward curved.

AERODYNAMIC PERFORMANCE:

Capacity: 283.0 ths. m³

Total pressure: 3099 Pa

Temperature: 250 C

Efficiency: 85 %

Dustiness: 2.0 g/m³

DIMENSIONS:

Length: 6510 mm

Width: 5340 mm

Height: 4820 mm

Weight: 13 800 kg

ELECTRIC MOTOR:

Power: 315 kW

Rate speed: 750 rpm

Moment of inertia: 1325 kg*m²

AUXILIARIES:
Actuator: 1600 Hm

DELIVERY OPTIONS:
Railway: Flatcar: 2 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

