

**Name:** IDFB-24x2-0.62-OG

**Russian name:** ДН-24x2-0,62ГМ

**Type:** Double inlet centrifugal ID fans of IDFB type

**Notes:** Backward curved blades



## DESCRIPTION:

Double inlet centrifugal ID Fans are intended to be used for flue gas removal from combustion chambers of solid fuel or gas-and-oil-fired boilers with the capacity of up to 480 t/h equipped with dry ash catchers. It is allowed to install such ID Fans in processing systems for handling compatible gases (The dustiness should be not more than 2 g/m<sup>3</sup>, abrasion and sticking tendency should be similar to ashed flue gases). Such ID Fans can be applied for single or serial-parallel operation. Double inlet centrifugal ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The main units of Double inlet centrifugal ID Fan are: running wheel, running gear, scroll casing, two inlet boxes and two guide vanes. The blades of impeller are backward curved.

## AERODYNAMIC PERFORMANCE:

Capacity: 368.0 ths. m<sup>3</sup>

Total pressure: 3707 Pa

Temperature: 250 C

Efficiency: 85 %

Dustiness: 2.0 g/m<sup>3</sup>

## DIMENSIONS:

Length: 6510 mm

Width: 5770 mm

Height: 5200 mm

Weight: 15 700 kg

## ELECTRIC MOTOR:

Power: 500 kW

Rate speed: 750 rpm

Moment of inertia: 1925 kg\*m<sup>2</sup>

**AUXILIARIES:**

Actuator: 1600 Hm

**DELIVERY OPTIONS:**

Railway: Flatcar: 3 | Open wagon: 0 | Schnabel car: 0

**DIMENSIONAL DRAWING:**

