www.russol.org

IDFB-26x2-F-C-OG

Name: IDFB-26x2-F-C-OG
Russian name: ДН-26х2ФКГМ
Type: Double inlet centrifugal high pressure ID fans
Notes: Backward curved blades



DESCRIPTION:

Double inlet centrifugal ID Fans are intended to be used for flue gas removal from combustion chambers of solid fuel or gas-and-oil-fired boilers with the capacity of 320-480 t/h equipped with dry ash catchers. It is allowed to install such ID Fans in processing systems for handling compatible gases (The dustiness should be not more than 2 g/m3, abrasion and sticking tendency should be similar to ashed flue gases). Such ID Fans can be applied for single or serial-parallel operation. Double inlet centrifugal ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The main units of Double inlet centrifugal ID Fan are: running wheel, running gear, scroll casing, two inlet boxes and two guide vanes. The blades of impeller are backward curved.

AERODYNAMIC PERFORMANCE:

Capacity: 380.0 ths. m3
Total pressure: 6760 Pa
Temperature: 250 C
Efficiency: 78 %
Dustiness: 2.0 g/m3

DIMENSIONS:

Length: 7120 mm
Width: 6200 mm
Height: 5610 mm
Weight: 21660 kg

ELECTRIC MOTOR:


Power: 1000 kW
Rate speed: 750 rpm
Moment of inertia: 3500 kg*m2

Tel.: +7 (3852) 390 - 530
info@russol.org

AUXILIARIES:
Actuator: 1600 Нм

DELIVERY OPTIONS:
Railway: Flatcar: 3 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:



Tel.: +7 (3852) 390 - 530
info@russol.org