

Name: LPRF-80-75-6.3-E1-1.5

Russian name: ВЛ-4-75 №6,3 Исп.1, 1,5 кВт

Type: Low pressure radial fans

Notes: It is recommended to use vibration isolators of CVI-40 type in quantity of 4 pcs.



DESCRIPTION:

Low pressure radial fans of LPRF-80-75 type are widely used in air ventilation systems of industrial and civil buildings, in air conditioning systems and for other industrial and sanitary-engineering purposes. These low pressure fans are manufactured in right-hand and left-hand rotations with backward curved blades. In accordance with the field of application LPRF-80-75 type fans can be produced in the following modifications:

-
 - general purpose industrial modification (carbon steel)
-
 - corrosion-resistant modification (stainless steel)
-
 - explosion-proof modification (dissimilar metals)
-
 - explosion-proof and corrosion-resistant modification (dissimilar metals)
-
 - explosion-proof modification (aluminum alloys)
-
 - corrosion-resistant modification (titanium alloys)
-
 - heat-resistant modification (carbon steel)
-
 - heat-resistant and corrosion-resistant modification (stainless steel)

AERODYNAMIC PERFORMANCE:

Capacity: 5.9 ths. m³

Total pressure: 570 Pa

Temperature: 200 C

Efficiency: 71-83 %

Dustiness: 0.1 g/m³

DIMENSIONS:

Length: 905 mm

Width: 1150 mm

Height: 1172 mm

Weight: 111,1 kg

ELECTRIC MOTOR:

Power: 1,5 kW

Rate speed: 1000 rpm
Moment of inertia: n/a kg*m²

AUXILIARIES:
Actuator: n/a Hm

DELIVERY OPTIONS:
Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

