


Name: MPRF-280-46-4-SE-E1-2.2

Russian name: ВЦ 14-46 ДУ №4 Исп.1, 2,2 кВт

Type: Medium pressure radial ID fans

Notes: It is recommended to use vibration isolators of CVI-39 type in quantity of 4 pcs.



DESCRIPTION:

The smoke exhaust fans of MPRF-280-46-SE type are widely used in exhaust systems of ventilation in industrial and civil buildings. These medium pressure fans are manufactured in two modifications:

 - Modification 01 - for 120 minute removal of air-flue gas mixtures (up to 400 °C) in case of fire (carbon steel covered with heat-resisting enamel)

 - Modification 02 - for 90 minute removal of air-flue gas mixtures (up to 600 °C) in case of fire (stainless steel)

AERODYNAMIC PERFORMANCE:

Capacity: 6.8 ths. m³

Total pressure: 690 Pa

Temperature: 600 C

Efficiency: 62-71 %

Dustiness: 0.1 g/m³

DIMENSIONS:

Length: 796 mm

Width: 744 mm

Height: 796 mm

Weight: 72,8 kg

ELECTRIC MOTOR:

Power: 2,2 kW

Rate speed: 1000 rpm

Moment of inertia: n/a kg*m²

AUXILIARIES:

Actuator: n/a Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

