

Name: MPRF-280-46-6.3-E1-5.5**Russian name:** ВЛ-14-46 №6,3 Ичп.1, 5,5 кВт**Type:** Medium pressure radial fans**Notes:** It is recommended to use vibration isolators of CVI-41 type in quantity of 4 pcs.

DESCRIPTION:

Medium pressure radial fans of MPRF-280-46 type are widely used in air ventilation systems of industrial and civil buildings, in air conditioning systems and for other industrial and sanitary-engineering purposes. These medium pressure fans are manufactured in right-hand and left-hand rotations with backward curved blades. In accordance with the field of application MPRF-280-46 type fans can be produced in the following modifications:

-
 - general purpose industrial modification (carbon steel)
-
 - corrosion-resistant modification (stainless steel)
-
 - explosion-proof modification (dissimilar metals)
-
 - explosion-proof and corrosion-resistant modification (dissimilar metals)
-
 - explosion-proof modification (aluminum alloys)
-
 - corrosion-resistant modification (titanium alloys)
-
 - heat-resistant modification (carbon steel)
-
 - heat-resistant and corrosion-resistant modification (stainless steel)

AERODYNAMIC PERFORMANCE:

Capacity: 13.0 ths. m³

Total pressure: 990 Pa

Temperature: 200 C

Efficiency: 65-73 %

Dustiness: 0.1 g/m³

DIMENSIONS:

Length: 1254 mm

Width: 1150 mm

Height: 1172 mm

Weight: 241 kg

ELECTRIC MOTOR:

Power: 5,5 kW

Rate speed: 750 rpm
Moment of inertia: n/a kg*m²

AUXILIARIES:
Actuator: n/a Hm

DELIVERY OPTIONS:
Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

