


Name: RF-5-0.75

Russian name: БКР №5, 0,75 кВт

Type: Roof fans

Notes:



DESCRIPTION:

Roof fans are widely used in exhaust systems of ventilation of industrial and civil buildings, in processing lines and for other industrial and sanitary-engineering purposes. These low pressure fans are manufactured with backward curved blades. In accordance with the field of application these fans can be produced in the following modifications:

-
 - general purpose industrial modification (carbon steel)
-
 - corrosion-resistant modification (stainless steel)
-
 - explosion-proof modification (dissimilar metals)
-
 - explosion-proof and corrosion-resistant modification (dissimilar metals)
-
 - explosion-proof modification (aluminum alloys)
-
 - At customers request roof fans can be complemented with self-opening gate.

AERODYNAMIC PERFORMANCE:

Capacity: 5.7 ths. m³
Total pressure: 240 Pa
Temperature: 80 C
Efficiency: 65-88 %
Dustiness: 0.1 g/m³

DIMENSIONS:

Length: 720 mm
Width: 720 mm
Height: 674,5 mm
Weight: 62 kg

ELECTRIC MOTOR:

Power: 0,75 kW
Rate speed: 1000 rpm
Moment of inertia: n/a kg*m²

AUXILIARIES:

Actuator: n/a Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

