


Name: IDF-21.5x2-OG

Russian name: Д-21,5x2ГМ

Type: Double inlet centrifugal ID fans of IDF type

Notes: Forward curved blades



DESCRIPTION:

High-pressure single and double inlet ID Fans with forward-curved blades are designed for flue gas removal from combustion chambers of steam boilers with the capacity of up to 640 t/h with increased resistance of flue gas path. It is also allowed to install such ID Fans in processing systems for handling compatible gases (The dustiness should be not more than 2 g/m³, abrasion and sticking tendency should be similar to ashed flue gases). Also these fans are recommended to handle gases containing trace elements with sticking tendency. High-pressure single and double inlet ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side.

AERODYNAMIC PERFORMANCE:

Capacity: 350.0 ths. m³

Total pressure: 5960 Pa

Temperature: 250 C

Efficiency: 72 %

Dustiness: 2.0 g/m³

DIMENSIONS:

Length: 5260 mm

Width: 4720 mm

Height: 4100 mm

Weight: 10 240 kg

ELECTRIC MOTOR:

Power: 1000 kW

Rate speed: 750 rpm

Moment of inertia: 1500 kg*m²

AUXILIARIES:

Actuator: 1600 Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

