

Name: IDFB-31x2-OG
Russian name: ДН-31x2ГМ
Type: Double inlet centrifugal ID fans of IDFB type
Notes: Backward curved blades



DESCRIPTION:

Double inlet centrifugal ID Fans are intended to be used for flue gas removal from combustion chambers of solid fuel or gas-and-oil-fired boilers with the capacity of up to 480 t/h equipped with dry ash catchers. It is allowed to install such ID Fans in processing systems for handling compatible gases (The dustiness should be not more than 2 g/m³, abrasion and sticking tendency should be similar to ashed flue gases). Such ID Fans can be applied for single or serial-parallel operation. Double inlet centrifugal ID Fans can have right-hand or left-hand rotational direction. The right-hand rotation is in a clockwise order and it should be defined at electric motor side. The main units of Double inlet centrifugal ID Fan are: running wheel, running gear, scroll casing, two inlet boxes and two guide vanes. The blades of impeller are backward curved.

AERODYNAMIC PERFORMANCE:

Capacity: 727.0 ths. m³
Total pressure: 6760 Pa
Temperature: 250 C
Efficiency: 87 %
Dustiness: 2.0 g/m³

DIMENSIONS:

Length: 6876 mm
Width: 8190 mm
Height: 7240 mm
Weight: 22500 kg

ELECTRIC MOTOR:

Power: 2000 kW
Rate speed: 750 rpm
Moment of inertia: 5000 kg*m²

AUXILIARIES:
Actuator: 4000 Hm

DELIVERY OPTIONS:
Railway: Flatcar: 6 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

