


**Name:** RF-3.15-0.105

**Russian name:** БКР №3,15, 0,105 кВт

**Type:** Roof fans

**Notes:**



## DESCRIPTION:

Roof fans are widely used in exhaust systems of ventilation of industrial and civil buildings, in processing lines and for other industrial and sanitary-engineering purposes. These low pressure fans are manufactured with backward curved blades. In accordance with the field of application these fans can be produced in the following modifications:

- <br> - general purpose industrial modification (carbon steel)
- <br> - corrosion-resistant modification (stainless steel)
- <br> - explosion-proof modification (dissimilar metals)
- <br> - explosion-proof and corrosion-resistant modification (dissimilar metals)
- <br> - explosion-proof modification (aluminum alloys)
- <br> - At customers request roof fans can be complemented with self-opening gate.

## AERODYNAMIC PERFORMANCE:

Capacity: 1.1 ths. m<sup>3</sup>  
Total pressure: 246 Pa  
Temperature: 80 C  
Efficiency: 65-88 %  
Dustiness: 0.1 g/m<sup>3</sup>

## DIMENSIONS:

Length: 277,5 mm  
Width: 575 mm  
Height: 510 mm  
Weight: 15 kg

## ELECTRIC MOTOR:

Power: 0,105 kW  
Rate speed: 1400 rpm  
Moment of inertia: n/a kg\*m<sup>2</sup>

AUXILIARIES:

Actuator: n/a Hm

DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

