


**Name:** RF-5-SE-0.75  
**Russian name:** ВКР ДУ №5, 0,75 кВт  
**Type:** Roof ID fans  
**Notes:**



## DESCRIPTION:

The smoke exhaust roof fans of RF type are widely used in exhaust and general systems of ventilation in industrial and civil buildings. These low pressure fans are manufactured in two modifications:

<br> - Modification 01 - for 120 minute removal of air-flue gas mixtures (up to 400 °C) in case of fire

<br> - Modification 02 - for 90 minute removal of air-flue gas mixtures (up to 600 °C) in case of fire

## AERODYNAMIC PERFORMANCE:

Capacity: 5.7 ths. m<sup>3</sup>  
Total pressure: 240 Pa  
Temperature: 600 C  
Efficiency: 65-88 %  
Dustiness: 0.1 g/m<sup>3</sup>

## DIMENSIONS:

Length: 726 mm  
Width: 726 mm  
Height: 771 mm  
Weight: 98 kg

## ELECTRIC MOTOR:

Power: 0,75 kW  
Rate speed: 1000 rpm  
Moment of inertia: n/a kg\*m<sup>2</sup>

## AUXILIARIES:

Actuator: n/a Hm

## DELIVERY OPTIONS:

Railway: Flatcar: 1 | Open wagon: 0 | Schnabel car: 0

DIMENSIONAL DRAWING:

